

# Command Summary Card

For Unix, Linux®, and Windows®

6.1

## ESKER VSI-FAX®

### Command Summary Card

Command line help is available for VSI-FAX commands by typing the command name followed by «-?», as in vfx -?. For detailed information about any VSI-FAX command, refer to the **Esker VSI-FAX Reference Addendum**.

#### Usage: vfx [options] <file>

##### Options:

|               |                                                     |
|---------------|-----------------------------------------------------|
| -A alias      | phone-book person alias to send to                  |
| -B batchfile  | batch file to process                               |
| -C coverage   | coverage to use                                     |
| -c tagfile    | tagfile to process                                  |
| -d dest       | fax queue destination                               |
| -E resolution | send resolution                                     |
| -F filetype   | file type                                           |
| -G group      | phone-book group alias to send to                   |
| -g groupname  | name of group file on server                        |
| -H hostname   | hostname to connect to                              |
| -help tags    | list of valid tags                                  |
| -i            | interactive cover-tag entry                         |
| -L resource   | list resource                                       |
| -l length     | page length                                         |
| -M mailaddr   | mail address to send to                             |
| -m mode       | mail notify mode                                    |
| -N            | scan file for phone-number                          |
| -n dialstring | phone number to send to                             |
| -O            | send coverage page only                             |
| -o filename   | image request and output to file                    |
| -p priority   | priority                                            |
| -R            | recover saved jobs                                  |
| -r retry      | retry method (default is "default")                 |
| -S on off     | enable scanning of stdin for tags (default is "on") |
| -s            | silent mode                                         |
| -t tag=value  | tag parameter                                       |

|             |                                     |
|-------------|-------------------------------------|
| -T string   | send time ([yy][mmdd hhmm[am   pm]) |
| -U username | user name                           |
| -u          | use user-configuration file         |

##### Modes:

|      |                                |
|------|--------------------------------|
| both | email always sent              |
| each | email sent for each attempt    |
| fail | email sent if failed (default) |
| none | email never sent               |
| ok   | email sent if successful       |

#### Usage: vfxstat [options] <reqid>

##### Options:

|             |                                                      |
|-------------|------------------------------------------------------|
| -a          | show admin information                               |
| -A          | show actual device in class being used to send a fax |
| -c secs     | continuous display every "secs"                      |
| -g          | show group jobs only                                 |
| -H hostname | hostname to connect to                               |
| -h          | display full-screen help line                        |
| -L language | specify language for time format                     |
| -l          | show local jobs only                                 |
| -q queue    | show count of jobs in queue ("all" for all)          |
| -r          | show only whether scheduler is up                    |
| -s secs     | continuous display every "secs" (full-screen)        |
| -T template | show status for reqid according to template          |
| -t          | show full listing                                    |
| -u user     | show jobs for user only                              |
| -U username | user name                                            |

#### Usage: vfxolog [options] <reqid>

##### Options:

|                 |                                                                            |
|-----------------|----------------------------------------------------------------------------|
| -a              | show all entries                                                           |
| -A <server dir> | alternate directory for OLOG databases                                     |
| -d              | show detail entries                                                        |
| -F spec         | output format (specify csv, pipe, tab, eval, tcl, xml, fmt=str or tpl=str) |

|                     |                                                                      |
|---------------------|----------------------------------------------------------------------|
| -f fields           | specify field list                                                   |
| -G group-id         | show members for group                                               |
| -g                  | show group entries                                                   |
| -H hostname         | hostname to connect to                                               |
| -h on off           | display header                                                       |
| -L language         | specify language for time format                                     |
| -l num              | output "num" lines per page                                          |
| -N                  | add filenames & pages to dump                                        |
| -O                  | add filenames to dump                                                |
| -r                  | show entries in reverse order                                        |
| -t <tag><op><value> | tag to match. Valid operations are: "=", "!", ">", "<", ">=", & "<=" |
| -U username         | user name                                                            |
| -u user             | show jobs for user only                                              |
| -v                  | show entries as they are deleted                                     |
| -X                  | mark entry "deleted"                                                 |
| -x                  | show expired jobs                                                    |
| Reqid               | if specified, list for reqid only                                    |

Usage: vfxilog [options] <reqid>

Options:

|                     |                                                                            |
|---------------------|----------------------------------------------------------------------------|
| -A <server dir>     | alternate directory for ILOG databases                                     |
| -d                  | show DID                                                                   |
| -F spec             | output format (specify csv, pipe, tab, eval, tcl, xml, fmt=str or tpl=str) |
| -f fields           | specify field list                                                         |
| -H hostname         | hostname to connect to                                                     |
| -h on off           | display header                                                             |
| -L language         | specify language for time format                                           |
| -l num              | output "num" lines per page                                                |
| -r                  | show entries in reverse order                                              |
| -t <tag><op><value> | tag to match. Valid operations are: "=", "!", ">", "<", ">=", & "<="       |
| -U username         | user name                                                                  |
| -u user             | show jobs for user only                                                    |
| -x                  | show deleted jobs                                                          |
| reqid               | if specified, list for reqid only                                          |

Usage: vfxprint [options] <file>

Options:

|           |                                         |
|-----------|-----------------------------------------|
| -d        | driver-name specify output driver       |
| -H        | no header box info when not scaled      |
| -l length | page length                             |
| -o option | provide driver-specific options         |
| -p range  | select page range to be printed         |
| -S        | scale output to full page               |
| -SS       | scale output to full page, edge-to-edge |

Driver-names:

|        |                                               |
|--------|-----------------------------------------------|
| pcl    | PCL raster                                    |
| pcl-sf | PCL faxfont                                   |
| ps     | PostScript™ at 300 DPI                        |
| epson  | Epson LQ Dot matrix                           |
| imagex | VSI image export mode (cannot output to pipe) |
| gdi    | Windows GDI                                   |

Usage: vfxtry [options] <reqid>

Options:

|             |                        |
|-------------|------------------------|
| -d dest     | new destination        |
| -H hostname | hostname to connect to |
| -n number   | new phone number       |
| -p priority | new priority           |
| -T sendtime | new sendtime           |
| -U username | user name              |
| reqid       | request to try/modify  |

Usage: vfxcancel [options] <reqid>

Options:

|                   |                            |
|-------------------|----------------------------|
| -g                | reqid is for a group       |
| -H hostname       | hostname to connect to     |
| -s <start>--<end> | cancel jobs in seqno range |
| -t <start>--<end> | cancel jobs in time range  |

|             |                   |
|-------------|-------------------|
| -u user     | cancel for <user> |
| -U username | user name         |
| -v          | verbose           |
| -x          | expire the job    |
| reqid       | request to cancel |

Usage: vfxsched [options] <cmd>

Options:

|    |                                         |
|----|-----------------------------------------|
| -a | send commands to admin server (vadmind) |
| -D | enable debug mode                       |
| -f | send commands to fax server (vrsched)   |
| -I | rebuild databases before startup        |
| -s | silent mode                             |

Cmds:

|                |                    |
|----------------|--------------------|
| Check          | check if running   |
| Halt           | halt the server    |
| List           | list all daemons   |
| restart [secs] | restart the server |
| start [secs]   | start the server   |
| stop [secs]    | stop the server    |
| version        | output version     |

If no cmd is given, "start" is assumed



Copyright © 1989-2009 Esker, S.A. All rights reserved. Use and duplicate only in accordance with the Software License Agreement - VSI-FAX; Copyright © 2000 The Apache Software Foundation. All rights reserved; Copyright © 2001 James Clark; Copyright © 2001 GNU Ghostscript; Copyright © 1989, 1991 Free Software Foundation, Inc.; Copyright © 1990, Regents of the University of Michigan. All rights reserved; Copyright © 2000, Microsoft Corporation. All rights reserved; Copyright © 1998-2008 The OpenSSL Project. All rights reserved; Copyright © 1995-1998 Eric Young (eay@cryptsoft.com) All rights reserved. Copyright © 1990-2008 Tech Know Systems, Ltd. Co.